



**Best DTF printer
for best production**

DTF -A30

Configuration item	Machine details
Model	DTF-A30
Print width	300mm
Print head	2 Epson F1080 heads
Print speed	8-12 sqm/h
Ink colors	CMKY +W
Ink type	Pigment ink
Rip software	Flexiprint/Cadlink/Maintop
Consumption	CMYK is 15-20ml/sqm, CMYK+W is 25ml/sqm
Dimension	DTF-A30: 1000*640*640mm D300: 800*600*720mm



DTF -C30

Configuration item	Machine details
Model	DTF-C30
Print width	300mm
Print head	2 Epson I1600-A1 heads
Print speed	8-12 sqm/h
Ink colors	CMYK+W
Ink type	Pigment ink
Rip software	Flexiprint/Cadlink/Maintop
Consumption	CMYK is 15-20ml/sqm, CMYK+W is 25ml/sqm
Dimension	DTF-C30: 1570*870*730mm Shaker: 1730*950*1260mm



DTF -A60

Configuration item

Machine details

Model	DTF-A60
Print width	600mm
Print head	2/3/4 pcs Epson I3200-A1
Print speed	2/3pcs Printhead 6-10sqm/h 4 pcs Printhead 8-20sqm/h
Ink colors	CMYK+W
Ink type	Pigment ink
Rip software	Riin/Flexiprint/Cadlink/Maintop
Consumption	CMYK is 15-20ml/sqm, CMYK+W is 25ml/sqm
Dimension	1895*740*850mm



2 pcs I3200-A1 head

3 pcs I3200-A1 head

4 pcs I3200-A1 head

DTF Powder Shaker

Configuration item	Machine details
Model	D600
Print Width	600mm
Advantage	Auto powder-recycling device
Take up function	Automatic inductive
Power Supply	220V 50-60HZ 3500W
Dimension	920*730*1170mm




Configuration item	Machine details
Model	H650 PRO
Heating size	600mm
Media	Hot melt powder and PET film
	Dual language touch screen
	Auto-returning powder device
Advantage	Automatic correction
	Front heating board, upper baking and curing
	Automatic take-up system
Power supply	110V/220V 50-60HZ 4000W
Dimension	1560*890*950mm



Purificateur d'air

Configuration item	Machine details
Model	J10
Noise	<50dB
Efficiency	99.9%
Porosity	0.1 micron
Core Components	Filter





DTF- UV PRINTER

DTF UV -F30

Configuration item	Machine details
Model	UV-F30
Print Width	300mm
Print Heads	2pcs*EPSON 1080
Print Speed	6 PASS 12sqm/hour; 8 PASS 8sqm/hour
Ripsoftware	Flexiprint/Cadlink/Maintop
Resolution	8/12 PASS
Ink Curing	LED curing Ink: CMYK+W+Varnish Ink
Power Supply	220V 50-60HZ 400W
Work Environment	20-30°C Humidity: 35%-65%
Ink Consumption	20ml/sqm/color
Dimension	1220*750*650mm



DTF UV-F604

Configuration item

Machine details

Model	UV-F604
Print width	600mm
Print Heads	3 PCS EPSON I3200-U1
Print Speed	6 PASS 10 sqm/hour
Ripsoftware	Riin/Flexiprint/Cadlink/Maintop
Resolution	6/8/12 PASS
Cooling	Water cooling+UVLED lamp
Ink	W+CMYK+Varnish Ink
Power supply	220V 50-60HZ 1800W
Work Environment	20-30°C Humidity: 35%-65%
Dimension	2360*860*860mm

